

# GRAS RA0173

1/8" Nosecone



Length: 17.4 mm  
Outer diameter: 3.5 mm  
Threading (mic. protection grid threading):  
M3.175x0.2  
Material: Stainless steel  
Weight: tbd

The RA0173 is specially designed and optimized for use with 1/8" microphones for sound pressure measurements, when high speed wind comes from one known direction e.g. in a wind tunnel.

## Introduction

Proper use of a microphone with a nosecone is to aim the nosecone towards the air flow. The nosecone has an inner threading and is installed by replacing the protection grid with the nosecone.

## Design

When a microphone is placed in a laminar flow, turbulence is created which in turn results in unwanted pressure variations on the diaphragm. By installing a nosecone, the pressure variations, caused by the turbulence starting at the stagnation point, are moved as far away from the diaphragm as possible. Theoretically this supports a "longer-the-better design", but in practice it is a compromise between practical size and obtaining a streamlined shape.

The design of our nosecones is based on requirements from the National Aeronautical Laboratory of the Netherlands (NLR), who investigated the classical sharp-tipped nosecone and concluded that with this design, the stagnation point is unpredictable i.e. the turbulence could emerge at any point on the surface and cause unwanted pressure variations, which could reach the diaphragm.

A new design with a blunt tip was developed. This forces a predictable stagnation point already at the tip. As this turned out to be a success and a great improvement compared to the classical design with a sharp tip, this is now specified in the NLR requirement TP 96320. The surface is high-gloss polished to further improve the aerodynamic performance.

If the turbulence reduction obtained by the nosecone is not sufficient or you have space restrictions, we suggest that you look for GRAS surface microphones and our new flush-mount

microphone concept. These alternatives are also relevant if you experience flutter problems with microphones provided with nosecones.

If you need to make sound pressure measurements in a free-field with air coming from many different directions, we suggest you look for GRAS windscreens.

## Quality & Warranty

GRAS accessories are made of stainless steel, alloys and high-quality composites. These items are covered by a 2 year warranty respecting their intended use.

On wear products like cables and windscreens, we offer a 6 month warranty.



# GRAS Worldwide

Subsidiaries and distributors in more  
than 40 countries

## HEAD OFFICE, DENMARK GRAS SOUND & VIBRATION

Skovlytoften 33  
2840 Holte  
Denmark  
Tel: +45 4566 4046  
[www.grasacoustics.com](http://www.grasacoustics.com)  
[gras@grasacoustics.com](mailto:gras@grasacoustics.com)

## USA GRAS SOUND & VIBRATION

5750 S.W. Arctic Drive  
Beaverton, OR 97005  
Tel: 503-627-0832  
Toll Free: 800-231-7350  
[www.grasacoustics.com](http://www.grasacoustics.com)  
[sales-usa@grasacoustics.com](mailto:sales-usa@grasacoustics.com)

## CHINA GRAS SOUND & VIBRATION

Room 303, Building T6  
Hongqiaohui, 990, Shenchang Road  
Minhang District, Shanghai  
China, 201106  
Tel: +86 21 64203370  
[www.gras.com.cn](http://www.gras.com.cn)  
[cnsales@grasacoustics.com](mailto:cnsales@grasacoustics.com)



## ABOUT GRAS SOUND & VIBRATION

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

**GRAS** Sound  
& Vibration