

GRAS 43AA-S2

CCP Ear Simulator Kit According to IEC 60318-1 & -2



Connection: 0 V/CCP
Volume: Complex
Dyn range: 25 dB(A) to 150 dB
ANSI: S3.7
IEC: 60318-1 & -2

The GRAS 43AA-S2 CCP Ear Simulator Kit is a complete test jig for acoustical measurements on telephone handsets and earphones. It includes an IEC 60318 Ear Simulator RA0039 which is individually calibrated according to the ITU-T Recommendation P.57 (08/96) "Series P: Telephone transmission quality, objective measuring apparatus: artificial ears.

The GRAS 43AA-S2 CCP Ear Simulator Kit according to IEC 60318-1 & -2 is a complete test jig for acoustical measurements on telephone handsets and earphones in accordance with:

- IEC60318-1 & -2 Electroacoustics – Simulators of human head and ear – Part 1: Ear simulator for the calibration of supraaural earphones, 1998-07
- ITU-T Recommendation P.57 (08/96) Series P: Telephone transmission Quality, Objective measuring apparatus: Artificial Ears

It consists of the following components:

- IEC 60318-1 & -2 [GRAS RA0039 Ear Simulator](#)
- [GRAS 40AO ½" Pressure Microphone](#)
- [GRAS 26CB ¼" Preamplifier](#)
- [GRAS RA0052 Test Jig](#)
- Mounting plates for circum-aural and supra-aural headphones

The Test Jig has an adjustable spring-loaded arm to exert a variable force on the test object.

An externally polarized version is available, [GRAS 43AA](#).

A version with a [GRAS 26AB](#) Preamplifier is available, [GRAS 43AA-S3](#).

| | | |
|--|---------------|-------------------------|
| Theoretical dynamic range lower limit with GRAS preamplifier | dB(A) | 25 |
| Theoretical dynamic range upper limit with GRAS CCP preamplifier | dB | 150 |
| Set sensitivity @ 250 Hz (± 3 dB) | mV/Pa | 12 |
| Set sensitivity @ 250 Hz (± 3 dB) | dB re 1V/Pa | -38.5 |
| Temperature range, operation | °C / °F | - 30 to 60 / -22 to 140 |
| Temperature coefficient @250 Hz | dB/°C / dB/°F | - 0.01 / -0.006 |
| Humidity range non condensing | % RH | 0 to 80 |
| ANSI standard | | S3.7 |
| ITU-T recommendations | | P.57 Type 1 |
| CE/RoHS compliant/WEEE registered | | Yes/Yes/Yes |
| Connector type | | BNC |
| Weight | g / oz | 1.65 / 58.202 |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included items

| | |
|-----------------------------|--------------------------|
| GRAS AA0070 | 3 m Microdot – BNC Cable |
|-----------------------------|--------------------------|

Optional items

| | |
|-----------------------------|--|
| GRAS RA0196 | Retrofit High-tension Spring Kit for RA0052 (for previous versions (before summer 2014)) |
|-----------------------------|--|

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK GRAS SOUND & VIBRATION

Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.grasacoustics.com
gras@grasacoustics.com

USA GRAS SOUND & VIBRATION

5750 S.W. Arctic Drive
Beaverton, OR 97005
Tel: 503-627-0832
Toll Free: 800-231-7350
www.grasacoustics.com
sales-usa@grasacoustics.com

CHINA GRAS SOUND & VIBRATION

Room 303, Building T6
Hongqiaohui, 990, Shenchang Road
Minhang District, Shanghai
China, 201106
Tel: +86 21 64203370
www.gras.com.cn
cnsales@grasacoustics.com



ABOUT GRAS SOUND & VIBRATION

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

GRAS Sound
& Vibration