GRAS 45BC-3

KEMAR Head & Torso with Mouth Simulator for Telephone Test, 1-Ch LEMO





Connection: Traditional Power Supply (200

V/LEMO) Channel(s): 1 ANSI: S3.36, S3.25 IEC: 60318-4

ITU-T Rec. P.57 Type 3.3 based on ITU-T Rec.

P.58

Special feature: Built-in power amplifier for

mouth simulator

The 45BC-3 KEMAR Head & Torso with Mouth Simulator for Telephone Test, 1-Ch LEMO is configured with pinnae and with IEC 60318-4 Ear Simulator and ear canal extension in the right ear. Due to the design of KEMAR, realistic measurement in a sound environment as experienced by a human being using a hearing aid is possible. In addition, the 45BC-3 is provided with a mouth simulator for testing of the microphone in the telephone. The 45EA handset positioning system is included. Its CCP equivalent is GRAS 45BC-4 KEMAR Head & Torso with Mouth Simulator for Telephone Test, 1-Ch CCP.



GRAS 45BC-3 KEMAR Head & Torso with Mouth Simulator for Telephone Test, 1-Ch LEMO

Introduction

The KEMAR head and torso simulator was introduced by Knowles in 1972 and quickly became the industry standard for hearing-aid manufacturers and research audiologists (visit KEMAR.us to read the full story). It is based on worldwide average human male and female head and torso dimensions. It meets the requirements of ANSI \$3.36/ASA58-2012 and IEC 60318-7:2011.

The current KEMAR Head and Torso has the same dimensions and acoustical properties as the original KEMAR, but has been developed further by GRAS to meet the industry's demand for realistic measurements of hearing aids, headphones, and headsets. It provides acoustic diffraction similar to that encountered around the median human head and torso, both in the proximity and in the far-field.

As all the preconfigured 45BC KEMARs consist of the same basic 45BC KEMAR Non-configured, plus a set of application-specific accessories, the full information about a given KEMAR configuration is obtained by combining the information about the 45BC KEMAR Non-configured and the information for a given configured version as found in the present text. Read about the non-configured KEMAR here.

Design

The 45BC-3 is a KEMAR Head & Torso with Mouth Simulator for Telephone Test, with externally polarized ear simulator and large straight pinnae. A special feature of this configuration is the 45EA Handset Positioning System.

45BC-3 is delivered fully configured, individually calibrated and ready for use. In addition to a system calibration certificate, a USB flash memory with simulation data is included.

The main configuration specific components of the 45BC-3 are the 44AA Mouth Simulator, the RA0045 Ear Simulator According to 60318-4, the KB1065/KB1066 Large Straight Pinnae and the 45EA Handset Positioning System.

The 44AA Mouth Simulator according to ITU-T Rec. P51 with built-in power amplifier

The maximum continuous signal the mouth can produce in 1/3-octave bands is 100dB re. $20\mu Pa$ in the frequency range of 100Hz to 16kHz. Its loudspeaker accepts an external signal either directly or via its own built-in power amplifier (when power is applied).

The 60318-4 Ear Simulator

The acoustic input impedance of the RA0045 Ear Simulator closely resembles that of the human ear and, as a result, loads a sound source in very much the same way.

It complies with IEC 60318-4 and is measured and calibrated according to ITU-T P.57. It embodies a number of carefully designed volumes connected via well-defined and precisely tuned resistive grooves. In an equivalent electrical circuit, capacitors would represent the volumes, and inductance and resistance would represent respectively air mass and air flow within the resistive groves.

Read more about the RA0045 Ear Simulator.

The KB0065/KB0066 Pinnae

The KB0065 and KB0066 are large straight pinnae for use with a straight ear canal extension. The hardness is 35 Shore 00. They comply with the IEC and ITU-T recommendations.

The 45EA Handset Positioning System



Technology

The 45EA Handset Positioning System is designed for the head and torso simulator with Mouth Simulator. With this combination, you can make very realistic in-situ measurements on mobile telephones as well as conventional handsets.

You can mount the system on the KEMAR without additional tools. The system can be mounted on either side of KEMAR, and you can easily switch it from one side to the other side.

Read more about the <u>45EA Handset Positioning</u> <u>System.</u>

Other accessories for this configuration are listed in the Ordering Info tab.

Performance and warranty

KEMAR is made of components from our standard portfolio, all manufactured of high-quality material and branded parts that were chosen and processed to ensure life-long stability and robustness. This enables us to offer 2 years warranty against defective materials and workmanship. Exceptions: Microphones included in KEMAR as for these our normal 5-year warranty apply. The warranty period for cables is 6 months.



Specifications

| | | ······································ |
|--|-------------|---|
| Connector type | | 7-pin LEMO (FGG.1B.307) |
| Set sensitivity @ 250 Hz (±2 dB) | mV/Pa | 12.5 |
| Set sensitivity @ 250 Hz (±2 dB) | dB re 1V/Pa | -38.5 |
| Theoretical dynamic range lower limit with GRAS preamplifier | dB(A) | 25 |
| Theoretical dynamic range upper limit with GRAS preamplifier @ +28 V / ±14 V power supply | dB | 151 |
| Theoretical dynamic range upper limit with GRAS preamplifier @ +120 V / ±60 V power supply | dB | 163 |
| Resonance frequency | kHz | 13.5 |
| Temperature range, operation | °C/°F | -30 to 60 / -22 to 140 |
| Temperature range, storage | °C / °F | -40 to 65 / -40 to 149 |
| Humidity range non condensing | % RH | 0 to 95 |
| ANSI standard | | S3.36, S3.25 |
| IEC standard | | 60318-4 (former 60711), 60318-7 (former 60959) |
| ITU-T recommondations | | P.380 |
| Weight | g / oz | 11.45 k / 404 |
| MOUTH SIMULATOR | | |
| Output impedance | Ω | 8 |
| Maximum power, continuous | W | 10 |
| Maximum power, pulsed 2 sec. | W | 50 |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



Included items

| GRAS 45BC | KEMAR Head & Torso with <u>GRAS 44AA Mouth Simulator</u> , non-configured |
|---------------------|---|
| <u>GRAS KB1065</u> | KEMAR Large Right Ear 35 Shore 00 |
| <u>GRAS KB1066</u> | KEMAR Large Left Ear 35 Shore 00 |
| GRAS RA0237 | Straight Ear Canal Extension Kit for KEMAR (2 pcs) |
| GRAS RA0045 | IEC 60318-4 Ear Simulator |
| <u>GRAS 26AS-S3</u> | 1/4" Preamplifier, Short version with 0.4 m cable |
| GRAS GR0010 | Adapter for 1/2" Microphone and 1/4" Preamplifier |
| GRAS GR0408 | External Ear Canal (2 pcs) |
| GRAS GR0409 | Union Nut |
| GRAS AA0008 | LEMO 7-pin - LEMO 7-pin Cable, 3 m, 2 pcs |
| GRAS 45EA | Handset Positioning System for KEMAR |
| GRAS 46BP-1 | 1/4" LEMO Pressure Microphone Set |

Optional items

Power Modules for Externally Polarized Ear Simulators and Microphones

| GRAS 12AK | 1-Channel Power Module with gain, filters and SysCheck generator |
|-----------|--|
| GRAS 12AD | 1-Channel Power Module |
| GRAS 12AA | 2-Channel Power Module with gain, filters and SysCheck generator |
| GRAS 12AR | 2-Channel Power Module |
| GRAS 12AQ | 2-Channel Universal Power Module with signal conditioning and PC interface |

For Ear Simulator Calibration

| GRAS 42AP | Intelligent Pistonphone (250 Hz or 251.2 Hz, 114 dB +/- 0.05 dB) |
|-------------|--|
| GRAS 42AA | Pistonphone (250 Hz, 114 dB +/- 0.08 dB) |
| GRAS RA0157 | 1/2" Calibration Adapter for KEMAR Pinna |



Pinna Simulators

| GRAS KB0060 | KEMAR Small Right Ear 55 Shore 00 |
|--------------------|---|
| <u>GRAS KB0061</u> | KEMAR Small Left Ear 55 Shore 00 |
| GRAS KB0065 | KEMAR Large Right Ear 55 Shore 00 |
| <u>GRAS KB0066</u> | KEMAR Large Left Ear 55 Shore 00 |
| <u>GRAS KB1060</u> | KEMAR Small Right Ear, 35 Shore 00 |
| GRAS KB1061 | KEMAR Small Left Ear 35 Shore 00 |
| GRAS KB1065 | KEMAR Large Right Ear 35 Shore 00 |
| GRAS KB1066 | KEMAR Large Left Ear 35 Shore 00 |
| <u>GRAS KB0090</u> | KEMAR Large Right Ear (VA-Style/SQ) 55 Shore 00 |
| GRAS KB0091 | KEMAR Large Left Ear (VA-Style/SQ) 55 Shore 00 |
| GRAS KB1090 | KEMAR Large Right Ear (VA-Style) 35 Shore 00 |
| GRAS KB1091 | KEMAR Large Left Ear (VA-Style) 35 Shore 00 |

Ear Mould Simulators

| GRAS KB0110 | Ear Mould Simulator for 2 mm Inner diameter tubing |
|--------------------|--|
| <u>GRAS KB0111</u> | Ear Mould Simulator for 3 mm Inner diameter tubing |

Ear Canal Extension and Microphone Holder Kits (kits with 2 pcs and 0-rings)

| GRAS RA0237 | Straight Ear Canal Extension Kit for KEMAR |
|-------------|--|
| GRAS RA0238 | VA-tapered Ear Canal Extension Kit for KEMAR |
| GRAS RA0239 | Ear canal Extension Kit w. silicone lining for KEMAR |
| GRAS RA0240 | Holder for long 1/2" microphone Kit for KEMAR |
| GRAS RA0241 | Holder for short 1/2" microphone Kit for KEMAR |
| GRAS RA0243 | Holder for 1/2" microphone Kit for KEMAR |
| GRAS RA0244 | O-ring kit for KEMAR, 2 pcs. |



| GRAS RA0249 | Straight Ear Canal Extension Kit for KEMAR, made of POM, for binaural hearing aid test |
|-------------|--|
| GRAS RA0250 | Tapered Ear Canal Extension Kit for KEMAR, made of POM, for binaural hearing aid test |

KEMAR Retrofit Kit for Binaural Hearing Aid Test

| | KEMAR Retrofit Kit for Binaural Hearing Aid Test: |
|--------------------|---|
| GRAS RA0251 | The Kit includes Ear Holder Plates, mounting bolts and the RA0249 and RA0250 Ear Canal Exten- |
| | sion Kits. Included items are made of POM, Nylon and Teflon. |
| | |

Extension Cables

| GRAS AA0008 | LEMO 7-pin - LEMO 7-pin Cable, 3 m |
|--------------------|--|
| GRAS AA0009 | LEMO 7-pin - LEMO 7-pin Cablee, 10 m |
| GRAS AA0020- CL | LEMO 7-pin - LEMO 7-pin Cable, Customized Length xxxx cm |

Flight Case

| GRAS KM0094 | PELI Case for KEMAR |
|-------------|---------------------|

Simulation Model of KEMAR

| GRAS KB3000 | Simulation Model of KEMAR with large pinnae |
|-------------|---|
| GRAS KB3001 | Simulation Model of KEMAR with small pinnae |

Stand for KEMAR

| GRAS AL0026 Loudspeaker stand for KEMAR, & 35 mm |
|--|
|--|

Miscellaneous

| GRAS KB0000 | KEMAR Handbook |
|-------------|-------------------|
| GRAS KB0010 | T-Shirt for KEMAR |

GRAS Sound & Vibration reserves the right to change accessories without notice.



GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION

Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.grasacoustics.com gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION

5750 S.W. Arctic Drive Beaverton, OR 97005 Tel: 503-627-0832 Toll Free: 800-231-7350 www.grasacoustics.com sales-usa@grasacoustics.com

АИІН

GRAS SOUND & VIBRATION

Room 303, Building T6 Hongqiaohui, 990, Shenchang Road Minhang District, Shanghai China. 201106 Tel: +86 21 64203370 www.gras.com.cn



ABOUT GRAS SOUND & VIBRATION

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

GRAS Sound & Vibration