

F1B1B11A



Load Cell, 1-axial Location: Seat Belt

Force direction
Force (F)

Application
Measurement of forces at the seat belt
during automotive crash or sled tests

Equivalent types
Customized version

Measurement specification
Resistive
Strain gauges

Options
ID-Module integrated in sensor
Linearizing circuit (supply voltage: 5-10V)







Technical description

The strap is routed under two completely detachable shafts over the measurement body (sensor). The shafts can be detached using a ball locking device by pressing a button. The shafts can still be rotated in the locked state. The applied force causes strain of the measuring point of the base body. The deformation is measured using strain gauges. The wiring of multiple strain gauges for a full bridge circuit compensates for the temperature influence on the zero signal. The very light belt force sensor made of titanium minimizes the influence of the measuring system due to the low own weight of the sensor. The system-inherent non-linearity can be partially compensated for by an optional integrated linearization circuit. The standard version without linearization is already shipped with calibration according to ISO/ TS 17242 (third degree polynomial approximation).



Dimensions



Technical Data Sheet



F1B1B11A

Technical specification

	Unit	Linearizing circuit	
		without	with
Measuring range	kN	16	
Sensitivity ¹⁾	mV/V/kN	0.18	5.9
	mV/kN		
Output signal ^{1), 2)}	mV/V	2.9	95
	mV		
Bridge resistance	Ω	350	
Zero signal ¹⁾	mV/V	≤ 0.05	≤ 1.5
	mV		
Amplitude non-linearity ³⁾	%	≤ 3.0	≤ 1.0
Hysteresis ³⁾	%	–	–
Supply voltage	V	2–15	5–10
Ultimate load	%	150	
Insulation resistance	M Ω	> 100	
Temperature range	$^{\circ}\text{C}$	-30...+70	
Band thickness	mm	≤ 1.3	
Band width	mm	50.8 (2")	
Weight (approximate)	g	83	

All values measured at 10 V sensor supply voltage and at 23 $^{\circ}\text{C}$, with standard Berger 08022/2/0702 belt type.

¹⁾ Typical value

²⁾ At nominal load

³⁾ Relative nominal range