



## OS II

## Model OS II-1550

The OS II 1550 is a compact camera offering crisp, high-resolution images in buffered or streaming mode. With its flexible design, OStreaming cameras can connect to a host PC via the 10Gbps ethernet interface or to XStream camera infrastructure via the XStreamLink interface. Model 1550 comes standard with a Motorized MFT mount and supports up to 1440x1024 resolution at 4,850 fps in buffered mode. For high-G applications, the camera can be configured with an optional C mount. Additional connectivity options offer easy out-of-the box implementation for single or multi-camera installations.

- Compact form factor
- Flexible buffer or streaming options
- Motorized MFT Standard

### APPLICATIONS

Automotive, Research

### KEY FEATURES

Maximum Resolution	1440 x 1024
Maximum FPS @ Maximum Res	4,850 fps
Operating Temperature	-40+50°C / -40+122°F

### FRAME PROPERTIES

Sensor Type	CMOS - Proprietary
Sensor Size	17.5 x 9.85 mm
Sensor Format	1.3 inch
Pixel Size (micron)	9.12 x 9.12 µm
Pixel Depth	12 bit mono 36 bit color
Sensitivity	30,000 ISO Mono, 10,000 ISO Color
Min. Exposure Time	1µs (*Shorter integration optional)
Array	1.5 megapixel
Quantum Efficiency	60%

### MECHANICAL

Weight	0.4 kg or 0.9 lbs
Dimensions	72 x 64 x 85 mm (W x H x L)
Shock & Vibration	Shock: 200G / Vibration: 40G - All axes
Mount	Motorized MFT Mount (Standard), C Mount

### TRIGGERING AND SYNCHRONIZATION

Sync In	Phase-lock TTL, IEEE1588 UDP, 1PPS
Sync Out	Frame sync / Strobe
Trigger	TTL & Switch/Circular buffer with on-camera or software trigger



### POWER

Input Voltage	7-14VDC
---------------	---------

### COMMUNICATION INTERFACE

Ethernet	10 Gbps
----------	---------

### EMBEDDED LOGIC

Debayering	Color Cameras Only
Temporal Noise Reduction	Standard
Dynamic Noise Reduction	Standard
User defined ROI's and LUT's	Standard
Frame to frame Auto-Exposure and Motion Trigger	Standard

### SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF